

U.S. Tsubaki Power Transmission, LLC

**U.S. Tsubaki Holdings, Inc.**Corporate Headquarters

301 E. Marquardt Dr.

Wheeling, IL 60090 USA

Toll Free: 800.323.7790 Phone: 847.459.9500 Fax: 847.459.9515


Email: <a href="mailto:sales@ustsubaki.com">sales@ustsubaki.com</a>
Website: <a href="mailto:www.ustsubaki.com">www.ustsubaki.com</a>


## ITEM # RS40 WK-2, RS SINGLE PITCH ATTACHMENT CHAINS

## **RS ROLLER CHAIN ATTACHMENTS**

U.S. Tsubaki RS single pitch roller chains may be adapted for conveying duties by the addition of attachments. The standard types of attachments include bent or straight

+ more





## Specifications | Pin Specifications | Link Plate | Attachment Specifications

**Specifications** 

Attachment Number	WK-2
ANSI No.	40
P - Pitch	0.500 in

W - Width Between Roller Link Plates	0.312 in
R - Roller Diameter	0.312 in
Standard Connection	Spring Clip Type

Pin Specifications –				
	D	0.454 :		
	D	0.156 in		
	L1	0.325 in		
	L2	0.392 in		
Link Plate -				
	н	0.472 in		
	Т	0.060 in		

Attachment Specifications				
	С	0.500 in		
	0	0.141 in		
	S	0.315 in		
	X	0.701 in		
	Nw	0.970 in		
	Kw	0.500 in		
	Additional Weight per Attachment	0.014 lb/att		